

Model 4503 Accelerometer



SMT Mount Accelerometer
Silicon MEMS
Signal Conditioned Accelerometer
Low Noise, Micro-g Resolution



The **Model 4503** is an economical board mountable accelerometer with micro-g resolution. The output is signal conditioned and temperature compensated and offers an optional 2.5V reference for single-ended or differential output measurements. The model 4503 is available in ranges from $\pm 2g$ to $\pm 200g$ with a frequency response up to 1500Hz. The gas damped MEMS sensing element provides stable long-term performance.



FEATURES

- Board Mountable Accelerometer
- 8 to 32Vdc Excitation Voltage
- Gas Damping
- Ranges: $\pm 2g$ to $\pm 200g$
- DC Response
- Low Power Consumption
- 8 to 32Vdc Excitation Voltage

APPLICATIONS

- Low Frequency Monitoring
- Seismic Applications
- Tilt Measurements
- Machine Control
- Motion Analysis
- Test & Measurement Applications

dimensions



Model 4503 Accelerometer

performance specifications

All values are typical at +24°C, 100Hz and 12Vdc excitation unless otherwise stated. Measurement Specialties reserves the right to update and change these specifications without notice. Standard product parameters are described in PSC-1002 for Embedded DC Accelerometers.

Parameters

DYNAMIC

	±2	±5	±10	±20	±50	±100	±200	Notes
Range (g)	1000	400	200	100	40	20	10	
Sensitivity (mV/g)	0-150	0-250	0-350	0-600	0-800	0-1300	0-1500	±5%
Frequency Response (Hz)	700	800	1000	1500	4000	6000	8000	
Natural Frequency (Hz)	±0.5	±0.5	±0.5	±0.5	±0.5	±0.5	±0.5	
Non-Linearity (%FSO)	<3	<3	<3	<3	<3	<3	<3	
Transverse Sensitivity (%)	0.7	0.7	0.7	0.7	0.7	0.7	0.6	
Damping Ratio	5000	5000	5000	5000	5000	5000	5000	
Shock Limit (g)								

ELECTRICAL

Zero Acceleration Output (mV)	±100	±100	±100	±100	±100	±100	±100	Differential
Excitation Voltage (Vdc)	8 to 32	8 to 32	8 to 32	8 to 32	8 to 32	8 to 32	8 to 32	
Excitation Current (mA)	<5	<5	<5	<5	<5	<5	<5	
Bias Voltage (Vdc)	2.5	2.5	2.5	2.5	2.5	2.5	2.5	
Output Resistance (Ω)	<100	<100	<100	<100	<100	<100	<100	
Insulation Resistance (MΩ)	>100	>100	>100	>100	>100	>100	>100	@100Vdc
Residual Noise (μV RMS)	80	60	60	70	80	80	80	Passband
Ground Isolation	Isolated from Mounting Surface							

ENVIRONMENTAL

Thermal Zero Shift (%FSO/°C)	±0.040	±0.040	±0.040	±0.040	±0.040	±0.040	±0.040	(0 to 70°C)
Thermal Sensitivity Shift (%/°C)	±0.050	±0.050	±0.050	±0.050	±0.050	±0.050	±0.050	(0 to 70°C)
Operating Temperature (°C)	-20 to 85							
Compensated Temperature (°C)	0 to 70							
Storage Temperature (°C)	-40 to 100							

PHYSICAL

Case Material	FR4 Circuit Board, Nickel-Silver Cover
Weight (grams)	6.9
Mounting	SMT or Screw

Optional accessories: 101 Three Channel DC Signal Conditioner Amplifier

The information in this sheet has been carefully reviewed and is believed to be accurate; however, no responsibility is assumed for inaccuracies. Furthermore, this information does not convey to the purchaser of such devices any license under the patent rights to the manufacturer. Measurement Specialties, Inc. reserves the right to make changes without further notice to any product herein. Measurement Specialties, Inc. makes no warranty, representation or guarantee regarding the suitability of its product for any particular purpose, nor does Measurement Specialties, Inc. assume any liability arising out of the application or use of any product or circuit and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Typical parameters can and do vary in different applications. All operating parameters must be validated for each customer application by customer's technical experts. Measurement Specialties, Inc. does not convey any license under its patent rights nor the rights of others.

ordering info

PART NUMBERING Model Number+Range

4503-GGG

|
| _____ Range (010 is 10g)

Example: 4503-010
Model 4503, 10g